



DESCRIPTION	ACTUAL FRAME SIZE	ROUGH OPENING MINIMUM	ACTUAL UNIT SIZE OUTSIDE BRICKMOLD W/ INSWING DOOR	ACTUAL UNIT SIZE OUTSIDE BRICKMOLD W/ OUTSWING DOOR	ROUGH OPENING HEIGHT (INSWING OR OUTSWING) (STUD TO STUD)			ROUGH OPENING HEIGHT (INSWING OR OUTSWING) (OUTSIDE BRICKMOLD TO FLOOR)		
					6'8"	7'0"	8'0"	6'8"	7'0"	8'0"
2'6"	31- $\frac{1}{2}$ "	32"	34"	34- $\frac{3}{4}$ "	82"	86"	98"	82- $\frac{3}{4}$ "	86- $\frac{3}{4}$ "	98- $\frac{3}{4}$ "
2'8"	33- $\frac{1}{2}$ "	34"	36"	36- $\frac{3}{4}$ "	82"	86"	98"	82- $\frac{3}{4}$ "	86- $\frac{3}{4}$ "	98- $\frac{3}{4}$ "
3'0"	37- $\frac{1}{2}$ "	38"	40"	40- $\frac{3}{4}$ "	82"	86"	98"	82- $\frac{3}{4}$ "	86- $\frac{3}{4}$ "	98- $\frac{3}{4}$ "

NOTE: ROUGH OPENING HEIGHT IS FIGURED USING 1-1/8" TALL SILL



NEW CONSTRUCTION
STANDARD WOOD FRAME
ROUGH OPENING DIMENSION LAYOUT

DWG#	VIII-8
DATE	2-01-05
NAME	MJP
SECTION	VIII
PAGE	8